



RAINBOW

BITUMINOUS SOLUTION

PRODUCT NUMBER	SP-69 (OM-03)
TYPE	Bituminous varnish based on asphalt pitches.
USES	Anti-corrosive paint for cargo holds.
CHARACTERISTICS	1. Very fast drying. 2. Very good water and corrosion resistance. 3. Easy application.
FINISH	Gloss
COLOR	Black
FLASH POINT	Above 26°C (80°F)
SPECIFIC GRAVITY	Above 0.85 Kg/L
VISCOSITY	80 ~ 100 KU (25°C)
DRYING TIME	Set-to-touch 1 hr. Dry hard 3 hrs. (25°C)
OPTIMUM FILM THICKNESS	Wet 90 microns (3.6 mil) Dry 35 microns (1.4 mil)
THEORETICAL COVERAGE	42.0 m ² /Gal 11.1 m ² /L 12.3 m ² /Kg
OVERCOATING INTERVALS	Min. 4 hrs. (25°C)
VOLUME SOLIDS	Above 39 %
THINNER	No.805 Paint Thinner (OM-07)
THINNING RATE	0~5 % (cleaning tools excluded)
PRECEDING COATS	No.908 Wash Primer (SP-01/02)
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Airless Spray, Brush
FOR AIRLESS SPRAY	Tip Size Graco 615, 715 Air Pressure 3~5 Kg/cm ² Pump Ratio 45 : 1 or 33 : 1

YUNG CHI PAINT & VARNISH MFG.CO.,LTD

26. YEN HAI 3RD ROAD. KAOHSIUNG, TAIWAN

TEL : 886-7-8713181 FAX : 886-7-8715443