



RAINBOW

EOPXY MORTAR PUTTY

PRODUCT NUMBER	1026
TYPE	Three pack, solvent-less mortar putty based on epoxy resin, hardener, and fillers.
USES	Used for the sealing of the cement products and mortar ground.
CHARACTERISTICS	<ol style="list-style-type: none">1. Excellent applicability, pinhole-less thin film with one coat.2. Excellent adhesion with small shrinkage.3. Very good resistance to wear, alkalis and solvents.4. Excellent mechanical and physical properties.
COLOR	Natural colors
DENSITY	Above 1.1 Kg/L (mixture)
VISCOSITY	Paste (mixture)
DRYING TIME	Set-to-touch 6 hrs. Dry hard 12 hrs. Full cured 7 days (25)
OPTIMUM FILM THICKNESS	100 microns
OVERCOATING INTERVALS	Min. 8 hrs. (25)
THEORETICAL COVERAGE	1.1 Kg/m ²
MIXING RATIO	Base : Hardener : Powder = 40 : 20 : 40 (by wt.)
POT LIFE	30 minutes (mixture, 25)
THINNER	No.1005 Epoxy Thinner (SP-12)(cleaning tools only)
THINNING RATE	Don't add.
SUBSEQUENT COATS	No.1001 Epoxy Topcoat (EP-04) No.1015 Epoxy Coating, Solventless
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Trowel
NOTE	<ol style="list-style-type: none">1. Evenly mix base and hardener according to the mixing ratio then blend the fillers thoroughly.2. Avoid applying the paint in rainy weather or relative humidity exceeded 85% RH.3. Don't apply the putty before curing of the mortar, and when applying, a wet surface must be thoroughly dried.4. Please wear gloves to avoid touching skin when applying.

YUNG CHI PAINT & VARNISH MFG.CO.,LTD

26. YEN HAI 3RD ROAD. KAOHSIUNG, TAIWAN

TEL : 886-7-8713181 FAX : 886-7-8715443