



RAINBOW

COPPER FREE TIN FREE SELF-POLISHING A/F

PRODUCT NUMBER	SP-99CF
TYPE	A copper free tin free A/F based on special acrylic resin for aluminium ship
USES	For aluminium ship bottom
CHARACTERISTICS	<ol style="list-style-type: none">1. Dry fast . Easy application.2. non cuprous oxide can not affect aluminium ship .3. non tin compounds can not pollution ocean .
FINISH	Flat
COLOR	Dark Brown
FLASH POINT	Above 26 °C
SPECIFIC GRAVITY	1.4 kg/L Above
VISCOSITY	85 KU Above
DRYING TIME	Set-to-touch 1hr below Dry hard 4 hrs
OPTIMUM FILM THICKNESS	Wet 200 μ Dry 100 μ
THEORETICAL COVERAGE	18 m ² /Gal 5 m ² /L
OVERCOATING INTERVALS	Min. 6 hrs
THINNER	xylene
THINNING RATE	0 ~ 5 % (by wt.)
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Airless Spray , Brush , Roller
NOTE	<ol style="list-style-type: none">1. Mix base and rate according to maker standard stir thoroughly.2. Moisture , grease , sludge , old paint and rust must be thoroughly removed from substrate.3. Avoid applying the paint in rainy or humid weather or substrate excessively high to 40°C or low to 10°C.4. Avoid applying to insufficient drying of previous paint coats.

EPDM31SP99CF V1.0

YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181
FAX:886-7-8715443