



RAINBOW

HOLD PAINT, RED OXIDE

PRODUCT NUMBER	SP-57 (OH-73)
TYPE	Hold paint based on alkyd and special resins..
USES	Topcoat for cargo holds.
CHARACTERISTICS	<ol style="list-style-type: none">1. Tough film with good abrasion resistance.2. Good humidity resistance.3. Good resistance to oil and water.4. Good adhesion.5. Easy application.
FINISH	Gloss
COLOR	Brown
FLASH POINT	Above 30°C (86°F)
SPECIFIC GRAVITY	Above 1.10 Kg/L
VISCOSITY	70 ~ 85 KU (25°C)
DRYING TIME	Set-to-touch 2 hrs. Dry hard 6 hrs. (25°C)
OPTIMUM FILM THICKNESS	Wet 80 microns (3.20 mil) Dry 350 microns (1.4 mil)
THEORETICAL COVERAGE	47.3 m ² /Gal 12.5 m ² /L 11.4 m ² /Kg
OVERCOATING INTERVALS	Min. 10 hrs. (25°C)
VOLUME SOLIDS	Above 44 %
THINNER	No.805 Paint Thinner (OM-07)
THINNING RATE	5~10 % (cleaning tools excluded)
PRECEDING COATS	SP-54 High Red Lead Primer (OP-91) SP-56 Red Oxide Primer (OP-95) No.920 LZI Primer (OP-94)
STORAGE SHELF LIFE	Minimum 1 year under normal storage conditions.
APPLICATION METHOD	Airless Spray, Brush, Roller
FOR AIRLESS SPRAY	Tip Size Graco 621, 721 Air Pressure 3~5 Kg/cm ² Pump Ratio 45 : 1 or 33 : 1

YUNG CHI PAINT & VARNISH MFG.CO.,LTD

26. YEN HAI 3RD ROAD. KAOHSIUNG, TAIWAN

TEL : 886-7-8713181 FAX : 886-7-8715443