



# RAINBOW

## SOLVENT-BASED ACRYLIC PAINT, CLEAR

PRODUCT NUMBER	402
TYPE	The solvent-based clear paint based on weather and alkali resistant acrylic resin.
USES	Used for protection of cement wall colored solvent-based acrylic paint, gypsum or marl products.
CHARACTERISTICS	<ol style="list-style-type: none"><li>1. Fast drying and very good workability</li><li>2. Excellent water, weather resistance, and gloss retention.</li><li>3. Excellent adhesion to cement or gypsum or marl products.</li><li>4. Excellent resistance to alkalis.</li></ol>
APPEARANCE	Transparent liquid
MASS DENSITY	Above 0.9 Kg/L
DRYING TIME	Set-to-touch 1/2 hr.      Dry hard 2 hrs. (25°C)
OPTIMUM FILM THICKNESS	Wet 80 microns      Dry 30 microns
THEORETICAL COVERAGE	47.0 m <sup>2</sup> /Gal      12.5 m <sup>2</sup> /L      14.0 m <sup>2</sup> /Kg
OVERCOATING INTERVALS	Min. 3 hrs.
NON-VOLATILE CONTENT	Above 40%
THINNER	NO.807 Xylene
THINNING RATE	0~5%
STORAGE SHELF LIFE	Minimum 2 years under normal storage conditions.
APPLICATION METHOD	Spray, Brush, Roller.
NOTE	<ol style="list-style-type: none"><li>1. The moisture content of new constructed cement walls should be under 12% . If not, the application must wait for 2 or 3 weeks until the wall is dry completely. Otherwise, too much moisture and alkali may affect film's performance and adhesion.</li><li>2. Adhered moisture, grease, and dirt on substrate must be cleaned thoroughly.</li></ol>

EPDM040402XX V1.2

# YUNG CHI PAINT & VARNISH MFG. CO., LTD.

No.26, Yen Hai 3rd Road, Kaohsiung, Taiwan.  
<http://www.rainbowpaint.com.tw>

TEL:886-7-8713181  
FAX:886-7-8715443